



Alarm Security Camera with Light




Viewtron IP-AX8D

4K IP Camera with Motion Detection
Spotlight and Alarm Light
Audio Alarm Siren, 2 Way Audio



- H.265+/H265/H.264+/H264/ MJPEG coding
- 8mp / 4K Resolution IP Camera: 3840 × 2160
- 30 ~ 40m IR Night Vision or White Pspotlight Effective Range
- 3D DNR, true WDR, HLC, BLC, Defog and ROI coding
- 1CH audio input; 1CH audio output
- 1CH built-in speaker; 1CH built-in microphone; Audio Alarm; 2-Way Audio
- Built-in micro SD card slot, up to 256GB Cards Supported
- DC12V, PoE power supply
- IP66 Weatherproof Rated
- 2-Way Audio Communication from Mobile App
- Supports Live Remote Viewing and Recorded Video Playback via Mobile App for iPhone and Android
- Built-in AI Software: Human Detection, Car Detection, Face Detection / Recognition
- Built-in Alarm Light: Blue and Red Alarm Light warning (flashing alternately)
- Supports Custom Audio Sirens and Voice Warnings via SD Card Upload
- Built-in Spotlight / Floodlight
- Alarm Light and Spotlight can be triggered via human detection and vehicle detection



www.Viewtron.com

Viewtron by CCTV Camera Pros

7142 N Seacrest Blvd.
Lantana, FL 33462
United States of America

Tel: +1-561-433-8488
www.Viewtron.com

Fax: +1-800-942-0728
info@cctvcamerapro.net




SPECIFICATIONS


Specifications	Model	IP-AX8D
Camera		
Image Sensor		1 / 1.8" CMOS
Image Size		3840 × 2160
Electronic Shutter		1 / 4s ~ 1 / 1000000 s
Iris Type		DC Iris
Min. Illumination		0.006lux@F1.4, AGC ON, 0 lux with IR 0 lux with LED
Lens		2.8~12mm@F1.4
Field of View		Horizontal: 113°~46°; Vertical: 59°~26°; Diagonal: 136°~54°
Focus		Motorized
Lens Mount		Φ14
Wide Dynamic Range		120dB
BLC		Yes
HLC		Yes
Defog		Yes
Digital NR		2D/3D DNR
S/N Ratio		≥50dB
Angle Adjustment		Pan: 0°~360°; Tilt: 0°~75°; Rotation: 0°~360°
Image		
Video Compression		Main stream: H.265+ / H.265 / H.264+ / H.264 Sub/Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard		Baseline Profile/Main Profile/High Profile
Resolution		8MP(3840×2160), 6MP(3200×1800), 4MP(2688×1520), 2K(2560×1440), 1080P(1920×1080), 720P(1280×720), D1, VGA(640×480), 640×360, CIF, 480×240
Main Stream		8MP/6MP/4MP/2K/1080P(60Hz: 1~30fps; 50Hz: 1~25fps)
Sub Stream		1080P(60Hz/50Hz: 1~15fps)/720P/D1/640×360(60Hz: 1~30fps; 50Hz: 1~25fps)
Third Stream		720P(60Hz/50Hz: 1~15fps)/ D1/VGA/640×360/CIF/480×240(60Hz: 1~30fps; 50Hz: 1~25fps)
Bit Rate		64 Kbps ~ 12 Mbps
Bit Rate Type		VBR / CBR
Audio Compression		G711A / U
Image Settings		ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Flip, Image Mirror, NR, etc. adjustable through client software or web browser
ROI		Each ROI to be configured separately
Interfaces		
Network		RJ 45 10M/100M self-adaptive Ethernet port
Video Output		CVBS output (BNC × 1)
Audio		1CH audio input; 1CH audio output; 1CH built-in speaker; 1CH built-in microphone
Alarm		1CH alarm input; 1CH alarm output
Storage		Built-in micro SD card slot; up to 256GB
Reset		Yes
Functions		
Remote Monitoring		Mobile App iPhone and Android, Desktop Software Mac and Windows
Web Browser		IE11(plug-in required)/Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+
Online Connection		Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol		UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP, RTMP, HTTP, 802.1x, UPnP, HTTPS, HTTP POST, QoS
Interface Protocol		ONVIF
Storage		Network remote storage; micro SD card storage
Smart Alarm		Motion detection, sensor alarm, SD card error, SD card full, IP address conflict, cable connection, audio alarm, light alarm
General Function		Watermark, IP address filtering, video mask, heartbeat, password protection, image distortion correction, smart supplement light, disarming
Security		Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP
PoE		Yes, IEEE802.3af
Supplement light Range		IR Night Vision Effective Range: 30 ~ 40 m White spotlight / floodlight Effective Range: 30 ~ 40 m
Protection Grade		IP66

Intelligent Analytics				
Smart Event	Line crossing, region intrusion/entrance/exiting (human/vehicle classification) loitering detection, illegal parking detection, abandoned/missing object detection			
Statistics	Target counting by line/area, heat map			
Exception Detection	Scene change, video blur and abnormal color detection, audio exception			
Face Detection	Face detection and face capture			
Video Metadata	Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 5 motor vehicle features and 1 non-motor vehicle feature			
DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8~12mm(W)	76m(249ft)	31(102ft)	15m(49ft)	8m(26ft)
2.8~12mm(T)	187m(614ft)	75m(246ft)	37m(121ft)	19m(62ft)
Others				
Power Supply	DC12V/PoE			
Power Consumption	< 12.5W			
Storage Conditions	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)			
Operating Conditions	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)			
Dimensions (mm)	Ø111.5 × 99.6			
Weight (net)	Approx. 0.64KG			
Installation	Ceiling mounting; wall mounting			
Certificate	CE, FCC			
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006)			

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL